

RAPTOR™

4-Channel Bioidentification System

IDENTIFY: Biological Agents



RAPTOR 4-channel bioassay system

The RAPTOR™ is a portable, 4-channel fluorometric assay system that can be used for high-sensitivity monitoring of biological agents, toxins, explosives, and chemical contaminants. It is a careful integration of optics, fluidics, electronics, and software into one compact system for use in laboratory settings and field assays. This unit can automatically perform a user-defined, multi-step, assay protocol while simultaneously tracking fluorescently-tagged chemical reactions occurring on the surface of each of the system's four disposable optical waveguide sensors.

Using immunoassay techniques, toxins and markers such as *Y. pestis* F1 antigen

have been detected at levels below 1 ppb from samples of a few hundred microliters. Each waveguide may be functionalized with a different assay, allowing up to four different assays to be run simultaneously. The results of these assays are displayed on a four line x 16 character LCD. The RAPTOR can also be run from a desktop PC, via an RS-232 link, using Windows-based software that is provided with the system.

The RAPTOR uses a disposable plastic coupon containing four injection-molded optical waveguides. These wave-guides are functionalized with the desired chemistry and inserted into the coupon. They are then simultaneously interrogated using 635 nm light while monitoring the return fluorescent signal. To run an assay, the user simply inserts a coupon and presses the Run Assay key. Assays typically take between 10 to 15 minutes and the results are displayed on the four line x 16 character LCD for each of the four waveguides.

Windows-based software allows the user to graphically monitor data recovery while an assay is running.

For detailed technical information, please visit www.resrchintl.com.

FEATURES

- Compact, portable system (about the size of a car battery)
- Immunoassay-based biosensor for real time or near real time detection of microbial pathogens
- Typical assay times of 10-15 minutes
- Coupons may be reused if test results continue to be negative
- Successfully used with urine, whole blood, milk, marine water, 10% meat slurries and slurries of human waste.

APPLICATION AREAS

- Water quality monitoring
- Laboratory testing
- Food safety monitoring
- Medical
- Agriculture
- Environmental
- Homeland security
- Mailrooms
- UAV's (Unmanned Aerial Vehicles)

RAPTOR™ SPECIFICATIONS	
Parameter	Value
Use profile	Indoor/outdoor sample collection, transfer, and assay; storage of 63 assay recipes; user in full MOPP gear either walking or in slowly moving vehicle.
Physical size	18.6 cm L x 27.4 cm H x 17.3 cm W
Weight	5.6 kg (w/o battery), 6.45 with battery.
Operating temperature range	1 to 35°C
Storage range	-29°C to 66°C
Assay coupon	Four simultaneous assays, disposable, barcoded for assay identification. Coupon reseals upon removal for archival storage.
Fluids storage	On-board storage of buffer and reagent. Reagent stored at constant temperature in reusable phase-change thermal storage module.
Sensitivity	Dependent on analyte, 1 to 10 ppb is typical for toxins.
Assay time	Dependent on assay; 10 to 15 minutes is typical.
Data/command entry	Day-night visible keypad and display, usable in MOPP gear.
Visual	Liquid crystal display; display provides positive/negative/retest and identity for each agent.
Communication	RS-232 bi-directional serial link and RF telemetry capability via optional BioLink™ RF Data Radio.
Data storage	EEPROM retains raw/processed data for over 200 assays.
Batteries	BA-5590/U primary battery; or UBI 2590 rechargeable battery; or 82-265 Volt (47-63 Hz) AC lump-in-cord power supply. Lifetime 9 to 24 hours.
Humidity	20 to 90%, noncondensing.
Ancillary equipment	Nylon twill photographer's-style case, carry strap compatible with MOPP gear; weight 1.2 kg (2.6 lb.).
Accessories support	Three digital input lines and six software-controlled external drivers.
Survivability	MILSPEC 810-E
<i>Research International reserves the right to change specifications without prior notice.</i>	

Research International, Inc.

U.S. Headquarters Office

17161 Beaton Road SE, Monroe, WA 98272-1034
 Phone: 360-805-4930 • Fax: 360-863-0439
 Toll Free: 1-800-927-7831
 Email: info@resrchintl.com • Web: www.resrchintl.com

U.S. East Coast Office

Jon Tobelmann
 Phone: 703-625-8381
 Email: jontobelmann@resrchintl.com

To locate an international distributor, please contact our headquarters office.

