



TacBio™

Biological Aerosol Detector

Low Cost, Light Weight Aerosol Detection



TacBio: Tactical biological detector

THE TACBIO™ was developed by the U.S. government for military, homeland security, and public health applications. It is a compact and rugged portable biological particle detector that uses both diffractive scattering and natural biological fluorescence to monitor aerosol particulates and classify them as being of either biological or non-biological origin.

TacBio is extremely useful for tracking background levels of airborne non-biological and biological materials and providing an alarm and/or digital activation command to other equipment if there is a rapid increase in the aerosol background. It cannot identify the type of biological material detected, and for that reason it is correctly characterized as an aerosol “trigger.”

Operation may be monitored remotely using Windows-based software provided with the unit, and changes made to its operating characteristics as needed or desired. Signals may be transmitted wirelessly between the TacBio and a monitoring PC or other equipment using BioLink™ Bluetooth transmitters and receivers, or via RS-232 cables.

FEATURES

- Economical
- Light weight
- True “biological trigger” device
- No consumables
- Wireless communications capable

APPLICATION AREAS

- Military
- Homeland security
- Public Health

Research International Inc. is an official licensee of the U.S. government for the TacBio, and has the right to manufacture and sell the instrument worldwide.

For more detailed technical information, visit www.resrchintl.com.

TacBio Specifications	
Characteristic	Description
Operating principle	Aerosol particle counter with UV fluorescence signature detection
Particle size range	Respirable particle range
Threat identification	Aerosolized bacteria, spores, viruses, toxins.
Interferents	Interferent resistant to diesel smoke, pollen, silica dust.
Detection limit	100-300 ACPLA in natural environments, 20-30 ACPLA under laboratory test conditions.
Start-up time	1 minute.
Time to alarm	1 minute or less. A 30 minute historical baseline is used for alarm protocols
Sampling volume	1.2 liter per min of ambient air nominal
Communication	RS-232 or wireless BioLink
Data storage	Collected data is stored on a removable SD-type data card. A 1.0 GB card will store more than 5 years of aerosol data.
Alarms	Electronic digital alarm; Red LED and >100dB piezoacoustic alarm on unit
Power	4.8 watts at 13 VDC to 36 VDC. Can be used with BA-5590 primary battery; or UBI 2590 rechargeable battery. Operable on AC mains power or vehicle power with proper converter.
Continuous operating time (approximate)	Essentially unlimited if powered externally. With BA-5590 primary battery, 37 hours; with UBI-2590 rechargeable battery, 45 hours.
Pump life	30,000 - 40,000 operating hours.
Operating temperature range	-20°C to 50°C. Operation to 60°C is permitted up to a total time of 1000 hours.
Humidity	0 to 95% non-condensing
Consumables	None
Size	15.60 x 17.00 x 33.50 cm without inlet air stack attached; 15.60 x 17.00 x 40.00 cm with inlet stack attached 15.60 x 14.53 x 40.00 cm without handle
Weight	3.4 kg without battery / 4.4 kg with battery
Package	EMI-resistant aluminum shell
<i>Research International reserves the right to change specifications without prior notice.</i>	

Research International, Inc.

U.S. Headquarters Office

17161 Beaton Road SE, Monroe, WA 98272-1034
 Phone: 360-805-4930 • Fax: 360-863-0439
 Toll Free: 1-800-927-7831
 Email: info@resrchintl.com • Web: www.resrchintl.com

U.S. East Coast Office

Jon Tobelmann
 Phone: 703-625-8381
 Email: jontobelmann@resrchintl.com

To locate an international distributor, please contact our headquarters office.

